



INTATHERM SAFE TOUCH LEVER OPERATED BASIN MIXER TAP



HEALTHCARE



HTM64



COMMERCIAL



PRODUCT INFORMATION

IT1005CP

Sequential safe touch thermostatic basin mixer tap complete with paddle lever

IT1006CP

Sequential safe touch thermostatic basin mixer tap complete with with pin lever

SPECIFICATIONS

Minimum operating pressure 0.2 bar
 Maximum operating pressure 10.0 bar
 Max inlet temperature 85 C
 Inlet temperature range hot supply: 52 - 65 C /
 Cold supply: 0.5 - 20 C
 Max temperature differential (mix to hot) for fail safe 10 C
 Max pressure inlet differential 10:1
 Factory temperature setting 41 C
 Temperature adjustment range 30 C to 50 C
 Temperature stability +/- 2 degrees

MATERIAL

Brass

COLOUR/FINISH

Chrome

MANUFACTURER

Inta

FIXING

Basin mounted using back nut provided

APPROVALS

TMV3 Scheme Approval, WRAS Approved, HTM64 compliant, HBN Ref TP6

PRODUCT DIMENSIONS

H152 x D140mm

ADDITIONAL INFORMATION

The Intatherm safe touch thermostatic basin mixer tap, designed for both domestic and commercial applications. A new stylish design featuring Inta's proven anti scald technology, a safe touch body and a self draining spout. With three lever options available and a smooth function cartridge, the tap can be operated easily by either hand or elbow with proven thermostatic protection the tap is the ideal solution for less able facilities, sheltered accommodation and also domestic bathrooms.

